

Features

- 20V/7A,
 $R_{DS(ON)} = 17m\Omega(Typ.)@V_{GS}=4.5V$
 $R_{DS(ON)} = 23m\Omega(Typ.)@V_{GS}=2.5V$
- Low $R_{DS(ON)}$
- Super High Dense Cell Design
- Reliable and Rugged


Applications

- Power Management
- Battery Protection



Halogen-Free

Pin Description



Absolute Maximum Ratings

Symbol	Parameter		Rating	Unit
Common Ratings (T _A =25°C Unless Otherwise Noted)				
V _{DSS}	Drain-Source Voltage		20	V
V _{GSS}	Gate-Source Voltage		±10	
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-55 to 150	°C
I _S	Diode Continuous Forward Current	T _A =25°C	1.9	A
Mounted on Large Heat Sink				
I _{DP} ^①	300μs Pulse Drain Current Tested	T _A =25°C	22	A
I _D ^②	Continuous Drain Current(V _{GS} =4.5V)	T _A =25°C	7	A
		T _A =70°C	5.6	
P _D	Maximum Power Dissipation	T _A =25°C	1.5	W
		T _A =70°C	1	
R _{θJC}	Thermal Resistance-Junction to Case		-	°C/W
R _{θJA} ^③	Thermal Resistance-Junction to Ambient		83.5	°C/W
Drain-Source Avalanche Ratings				
E _{AS} ^④	Avalanche Energy, Single Pulsed		TBD	mJ


Electrical Characteristics ($T_A=25^{\circ}\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Test Condition	KS8205BB			Unit
			Min.	Typ.	Max.	
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	20			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =20V, V _{GS} =0V			1	μA
		T _J =125°C			30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	0.5	0.65	1.1	V
I _{GSS}	Gate Leakage Current	V _{GS} =±10V, V _{DS} =0V			±100	nA
R _{DS(ON)} ^⑤	Drain-Source On-state Resistance	V _{GS} =4.5V, I _{DS} =4A		17	23	mΩ
		V _{GS} =2.5V, I _{DS} =3A		23	30	mΩ
Diode Characteristics						
V _{SD} ^⑤	Diode Forward Voltage	I _{SD} =2A, V _{GS} =0V		0.76	1.2	V
t _{rr}	Reverse Recovery Time	I _{SD} =1A, dI _{SD} /dt=100A/μs		15		ns
Q _{rr}	Reverse Recovery Charge			6		nC
Dynamic Characteristics ^⑥						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz		1.4		Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =10V, Frequency=1.0MHz		525		pF
C _{oss}	Output Capacitance			105		
C _{rss}	Reverse Transfer Capacitance			80		
t _{d(ON)}	Turn-on Delay Time	V _{DD} =10V, I _{DS} =1A, V _{GEN} =4.5V, R _G =6Ω		10		ns
t _r	Turn-on Rise Time			15		
t _{d(OFF)}	Turn-off Delay Time			31		
t _f	Turn-off Fall Time			21		
Gate Charge Characteristics ^⑥						
Q _g	Total Gate Charge	V _{DS} =16V, V _{GS} =4.5V, I _{DS} =5A		8		nC
Q _{gs}	Gate-Source Charge			1.1		
Q _{gd}	Gate-Drain Charge			3.6		

- Notes:
- ① Pulse width limited by safe operating area.
 - ② Calculated continuous current based on maximum allowable junction temperature.
 - ③ When mounted on 1 inch square copper board, $t \leq 10\text{sec}$. The value in any given application depends on the user's specific board design.
 - ④ Limited by T_{Jmax} . Starting $T_J = 25^{\circ}\text{C}$.
 - ⑤ Pulse test; Pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
 - ⑥ Guaranteed by design, not subject to production testing.






Ordering and Marking Information

Device	Package	Packaging	Quantity	Reel Size	Tape width
KS8205BB	TSSOP8	Tape&Reel	3000	13"	12mm










Y =Year,2017-A,2018-B,etc.
WW =Week.
XXX =Lot number.

Typical Characteristics




Typical Characteristics




Package Information
TSSOP8


SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
D	2.87	3.00	3.10	0.113	0.118	0.122
E	4.30	4.40	4.50	0.169	0.173	0.177
b	0.17	0.25	0.30	0.007	0.010	0.012
c	0.09	0.15	0.20	0.004	0.006	0.008
E1	6.20	6.40	6.60	0.244	0.252	0.260
A	1.00	1.10	1.20	0.039	0.043	0.047
A1	0.05	0.10	0.18	0.002	0.004	0.007
A2	0.80	1.00	1.10	0.031	0.039	0.043
e	0.65 (BSC)			0.026 (BSC)		
L	0.40	0.60	0.80	0.016	0.024	0.031
H	0.25 (TYP)			0.01 (TYP)		
θ	0°	4°	8°	0°	4°	8°


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Diode Recovery Test Circuit and Waveforms



Gate Charge Test Circuit and Waveform



Customer Service

Kwansemi Semiconductor Co.,Ltd

Email:Sales@kwansemi.com

Web:www.kwansemi.com

DISCLAIMER:

Kwansemi reserves the right to change the specifications and circuitry without notice at any time. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.